



SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 453/2010)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : BATTERIE SPIT PULSA 800 LI-ION

Product code : SPIT-014582-018483.

The battery is considered to be an ARTICLE for the purposes of REACH.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Rechargeable lithium ion batteries.

1.3. Details of the supplier of the safety data sheet

Registered company name : SPIT PASLODE.

Address : 150, route de Lyon.26500.BOURG LES VALENCE.France.

Telephone : 0 810 102 102. Fax : 0 810 432 432.

Email : msds-reach@spit.com

<http://www.spit.fr>

Distributors Details:

STOCKade - Paslode

8 Orbit Drive, Rosedale 0632

Auckland, New Zealand

Phone: +64 9 477 3000

1.4. Emergency telephone number : 112.

Association/Organisation : European emergency number.

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Substance which releases flammable gases in contact with water, Category 2 (Water-react. 2, H261).

Acute oral toxicity, Category 4 (Acute Tox. 4, H302).

Acute dermal toxicity, Category 4 (Acute Tox. 4, H312).

Skin irritation, Category 2 (Skin Irrit. 2, H315).

Serious eye damage, Category 1 (Eye Dam. 1, H318).

Respiratory sensitisation, Category 1 (Resp. Sens. 1, H334).

Skin sensitisation, Category 1 (Skin Sens. 1, H317).

Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

Reacts violently with water (EUH014).

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS07



GHS05



GHS08



GHS02

Signal Word :

DANGER

Product identifiers :

EC 235-362-0

COBALT LITHIUM DIOXIDE

EC 202-510-0

ETHYLENE CARBONATE

EC 244-334-7

LITHIUM HEXAFLUOROPHOSPHATE(1-)

Hazard statements :

H261

In contact with water releases flammable gases.

H302

Harmful if swallowed.

H312

Harmful in contact with skin.

H315

Causes skin irritation.

H317

May cause an allergic skin reaction.

H318

Causes serious eye damage.

H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H412	Harmful to aquatic life with long lasting effects.
EUH014	Reacts violently with water.
Precautionary statements - General :	
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
Precautionary statements - Prevention :	
P223	Keep away from any possible contact with water, because of violent reaction and possible flash fire.
P261	Avoid breathing vapours.
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary statements - Response :	
P301 + P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P330	Rinse mouth.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P335 + P334	Brush off loose particles from skin. Immerse in cool water / wrap in wet bandages.
P342 + P311	If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
P362	Take off contaminated clothing and wash before reuse.
P370 + P378	In case of fire: Use ... for extinction.
Precautionary statements - Storage :	
P402 + P404	Store in a dry place. Store in a closed container.
Precautionary statements - Disposal :	
P501	Dispose of contents/container at a disposal facility in accordance with local regulations.

2.3. Other hazards

THE BATTERY IS AN ARTICLE CONTAINING AN INTEGRATED MIXTURE (electrolyte - REACH definition).

THE ELECTROLYTE IS CONSUMED DURING THE ARTICLE'S USE PHASE AND IS NOT REJECTED (unless the article is damaged).

THE ABOVE LABEL IS THEREFORE FOR INFORMATION PURPOSES in case the ARTICLE IS DAMAGED and should not be fixed to the article.

The rechargeable lithium ion batteries described in this SDS are sealed products that are not hazardous when used in accordance with the manufacturer's instructions.

Do not short circuit, pierce, incinerate, crush, submerge, forcefully discharge or expose to temperatures in excess of the operating range stated on the products. Risk of fire and explosion.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

Identification	(EC) 1272/2008	Note	%
CAS: 12190-79-3 EC: 235-362-0 COBALT LITHIUM DIOXIDE	GHS07, GHS08 Dgr Acute Tox. 4, H302 Skin Sens. 1, H317 Resp. Sens. 1, H334 Aquatic Chronic 3, H412		25 <= x % < 50
INDEX: 013-002-00-1 CAS: 7429-90-5 EC: 231-072-3 ALUMINIUM POWDER (STABILISED)	GHS02 Dgr Water-react. 2, H261 Flam. Sol. 1, H228	T [1]	10 <= x % < 25
CAS: 7440-50-8 EC: 231-159-6 REACH: 17-2119429821-40 COPPER		[1]	10 <= x % < 25

CAS: 7440-44-0 EC: 231-153-3 CARBONE		[1]	2.5 <= x % < 10
CAS: 7782-42-5 EC: 231-955-3 GRAPHITE		[1]	2.5 <= x % < 10
INDEX: 607-022-00-5 CAS: 141-78-6 EC: 205-500-4 REACH: 01-2119475103-46 ETHYL ACETATE	GHS02, GHS07 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH:066	[1]	2.5 <= x % < 10
CAS: 96-49-1 EC: 202-510-0 ETHYLENE CARBONATE	GHS05 Dgr Eye Dam. 1, H318		2.5 <= x % < 10
CAS: 21324-40-3 EC: 244-334-7 LITHIUM HEXAFLUOROPHOSPHATE(1-)	GHS06, GHS05 Dgr Acute Tox. 4, H302 Acute Tox. 3, H311 Skin Corr. 1B, H314 Skin Sens. 1, H317 EUH:014		2.5 <= x % < 10

Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

Other data :

Each battery consists of a sealed metal container containing chemical substances and components, some of which may be hazardous in the event of a leak.

There is no risk from being exposed to these batteries unless the seal containing the electrochemical elements is broken by exposure to excess temperatures or the accidental application of abusive electrical or mechanical constraints.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

If a battery is ruptured or opened, evacuate people from the contaminated zone and ensure maximum ventilation to eliminate any corrosive gases, smoke or unpleasant odours.

If this event is the result of an accident, follow the advice below:

In the event of exposure by inhalation :

In the event of massive inhalation of dust, remove the person exposed to fresh air. Keep warm and at rest.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

In the event of an allergic reaction, seek medical attention.

In the event of splashes or contact with eyes :

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.

Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Remove any soiled or splashed clothing immediately.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water, administer activated medical charcoal and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Flammable.

5.1. Extinguishing media

In the event of fire, use specifically suitable extinguishing agents. Never use water.

Keep packages cool when in the vicinity of flames.

Suitable methods of extinction

In the event of a fire, use :

- carbon dioxide (CO₂)
- water
- foam

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use :

- water
- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)
- hydrogen fluoride (HF)

5.3. Advice for firefighters

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid any contact with the skin and eyes.

Avoid inhaling dust.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Use drums to dispose of collected waste in compliance with current regulations (see section 13).

6.3. Methods and material for containment and cleaning up

Hermetically seal leaking batteries and any contaminated absorbent material in a plastic bag and eliminate it as Special Waste in accordance with local regulations.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of asthma, allergies and/or chronic or periodical breathing difficulties should not, under any circumstances, use these

mixtures.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Remove contaminated clothing and protective equipment before entering eating areas.

Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

Do not crush or pierce the batteries or short circuit their positive/negative terminals with conducting materials (e.g.: metals) as this can result in excessive heating.

Do not apply direct heat or solder. Do not burn batteries.

Do not mix different brands or types of battery. Do not mix new batteries with old batteries.

Store batteries in non-conductive trays (e.g.: plastic).

Do not disassemble, damage or mechanically degrade the batteries.

Fire prevention :

Handle in well-ventilated areas.

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Never pour water into this mixture.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Avoid eye contact with this mixture at all times.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

Never open the packages under pressure.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from food and drink, including those for animals.

Leave a suitable gap between the batteries and walls.

Temperatures in excess of 70°C may cause batteries to leak and rupture.

Store batteries in their original packaging until they are to be used; do not mix them as a short circuit can cause a fire, a risk of leaks or rupture.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

Comply with the manufacturer's recommendations and the operating temperature range.

Applying pressure that can deform the battery may result in a disassembly followed by ocular, dermal or laryngeal irritation.

Do not immerse the batteries in water.

The batteries are not intended to be recharged by any external power sources other than Li-ion chargers approved by the manufacturer.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
7429-90-5	2 mg/m ³	-	-	-	-
7440-50-8	0.2 mg/m ³	-	-	-	-
7782-42-5	2 mg/m ³	-	-	-	R
141-78-6	400 ppm	-	-	-	-

- Germany - AGW (BAuA - TRGS 900, 21/06/2010) :

CAS	VME :	VME :	Excess	Notes
141-78-6	400 ml/m ³	1500 mg/m ³	2(l)	DFG, Y

- Belgium (Order of 19/05/2009, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
7429-90-5	10 mg/m ³	-	-	-	-
7440-50-8	1 mg/m ³	-	-	-	-

7440-44-0	2 f/cc	-	-	-	-
7782-42-5	2 mg/m3	-	-	-	R
141-78-6	400 ppm	-	-	-	-

- France (INRS - ED984 :2008) :

CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
7429-90-5	-	10	-	-	-	-
7782-42-5	-	2 A	-	-	-	25
141-78-6	400	1400	-	-	-	84

- Switzerland (SUVA 2009) :

CAS	VME-mg/m3 :	VME-ppm :	VLE-mg/m3 :	VLE-ppm :	Temps :	RSB :
7429-90-5	3A mg/m3	-	-	-	-	B
7440-50-8	0,1 i	-	0,2 i	-	4x15	-
7782-42-5	2,5 a	-	-	-	-	-
141-78-6	1400	400	2800	800	4x15	-

- UK / WEL (Workplace exposure limits, EH40/2005, 2007) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
7429-90-5	2 mg/m3	-	-	-	-
7440-50-8	0.2 mg/m3	-	-	-	-
7440-44-0	4 mg/m3	-	-	-	R
141-78-6	200 ppm	400 ppm	-	-	-

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Before handling powders or dust emission, wear mask goggles in accordance with standard EN166.

Prescription glasses are not considered as protection.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Butyl Rubber (Isobutylene-isoprene copolymer)

Recommended properties :

- Impervious gloves in accordance with standard EN374

Use personal protective equipment in the event of an electrolyte leak.

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

Wear protective clothing against solid chemicals and particles suspended in the air (type 5) in accordance with standard EN13982-1 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

Use personal protective equipment in the event of an electrolyte leak.

- Respiratory protection

Avoid breathing dust.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Type of FFP mask :

Wear a disposable half-mask dust filter in accordance with standard EN149.

Category :

- FFP1

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :

Physical state :	Solid.
Odour:	Odour-free (except if the product is damaged and there is an electrolyte leak)
-	Prismatic or cylindrical shaped batteries.

Important health, safety and environmental information

pH :	Not relevant.
Flash point interval :	Not relevant.
Vapour pressure (50°C) :	Below 110 kPa (1.10 bar).
Density :	> 1
Water solubility :	Insoluble.

9.2. Other information

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

This mixture reacts violently with water.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Avoid :

- humidity
- heat

Protect from moisture. Reaction with water can cause an exothermic reaction.

Dusts can form an explosive mixture with air.

10.5. Incompatible materials

Keep away from :

- water
- strong acids
- alkalis
- oxidising agents

Reacts violently with water.

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)
- hydrogen fluoride (HF)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Harmful if swallowed.

Harmful in contact with skin.

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

May have irreversible effects on the eyes, such as tissue damage in the eye, or serious physical decay of sight, which is not fully reversible by the end of observation at 21 days.

Serious eye damage is typified by the destruction of cornea, persistent corneal opacity and iritis.

May cause hypersensitivity of the respiratory tracts with effects taking the form of asthma, rhinitis/conjunctivitis or alveolitis.

May cause an allergic reaction by skin contact.

11.1.1. Substances

No toxicological data available for the substances.

11.1.2. Mixture

Acute toxicity :

Oral route : Harmful if swallowed.
300 < LD50 <= 2000 mg/kg

Dermal route : Harmful in contact with skin.
1,000 < LD50 <= 2000 mg/kg

Respiratory or skin sensitisation :

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

SECTION 12 : ECOLOGICAL INFORMATION

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity

12.1.1. Substances

No aquatic toxicity data available for the substances.

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

German regulations concerning the classification of hazards for water (WGK) :

WGK 2 (VwVwS vom 27/07/2005, KBws) : Hazardous for water.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

Do not incinerate or submit elements to temperatures in excess of 70°C. An excess temperature may damage the seal, cause a leak and/or cause elements to explode.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2015 - IMDG 2014 - ICAO/IATA 2015).

14.1. UN number

3480

14.2. UN proper shipping name

UN3480=<UNKNOWN>

14.3. Transport hazard class(es)

- Classification :



9

14.4. Packing group

-

14.5. Environmental hazards

-

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	9	M4	-	9	-	0	188 230 310 348 376 377 636	E0	2	E
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ			
	9	-	-	0	F-A,S-I	188 230 310 348 376 377	E0			
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	
	9	-	-	See 965	See 965	See 965	See 965	A88 A99 A154 A164 A183	E0	
	9	-	-	Forbidden	Forbidden	-	-	A88 A99 A154 A164 A183	E0	

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15 : REGULATORY INFORMATION**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Containers to be fitted with a tactile warning of danger (see EC Regulation No. 1272/2008, Annex II, Part 3).

- Particular provisions :

No data available.

- German regulations concerning the classification of hazards for water (WGK) :

WGK 2 (VwVwS vom 27/07/2005, KBws) : Hazardous for water.

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H225	Highly flammable liquid and vapour.
H228	Flammable solid.

H261	In contact with water releases flammable gases.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
EUH014	Reacts violently with water.
EUH066	Repeated exposure may cause skin dryness or cracking.

Abbreviations :

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).

GHS02 : Flame

GHS05 : Corrosion

GHS07 : Exclamation mark

GHS08 : Health hazard